an [adjustable] insulation sleeve positioned on an exterior of [one of] the primary [or secondary antennas] antenna; and

[an energy source; and]

A1. one or more cables [connecting the multiple antenna device with the energy source] coupled to the multiple antenna.

---

42. ~~16.~~ (Amended) The apparatus of claim [1] ~~47~~ 41, further comprising:

A2. a multiplexer coupled to the primary antenna, secondary antenna, and the [power supply] energy source to multiplex energy delivered to the primary and secondary antennas.

---

43. ~~19.~~ (Amended) The apparatus of claim [1] ~~47~~ 41, further comprising:

A3. one or more sensors positioned at one of an interior or an exterior of the primary or secondary antennas to detect one of impedance or temperature; and

resources connected with the sensors, the antennas and the energy source, the resources providing an output for delivering and maintaining a selected energy at the antennas.

Sub B8

31. (Amended) An ablation apparatus, comprising:

A4. a multiple arm device [of adjustable length] including a primary arm [with an adjustable length] and a longitudinal axis, and a secondary arm [with an adjustable length, the secondary arm adapted] coupled to the primary arm and configured to be deployed in a direction that is lateral to the longitudinal axis, wherein the secondary arm is constructed to be less structurally rigid than the primary arm [and the adjustable length of the primary and secondary arms permits a desired geometric ablation of a selected tissue mass];

an energy source; and

one or more cables [connecting the multiple arm device with] coupling the energy source with the multiple arm device.

---

7. 1
~~39.~~ (Amended) The apparatus of claim ~~31~~, wherein at least one of the primary or

A5. secondary arms is hollow and [adapted] configured to receive an infusion medium from an infusion source to introduce the infusion medium into a selected tissue mass.

---

11. 1
~~43.~~ (Amended) The apparatus of claim ~~31~~, further comprising:

A6. one or more sensors positioned at one of an interior or an exterior of the primary or secondary arms; and

resources [connected] coupled with the sensors, the energy source and at least one of

27